





This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
5		AS DRAWN BY CANAM	7/18/2013	CFS	
6	14-0101	CH'D TITLE BLOCK WAS RED BARN IS DART. ADDED MACHINE ENGRAVE NOTE.	7/30/2014	DJN	RW
7	17-0081	ADDED DIM 4X R.13.	4/6/2017	RJC	JAG



#### NOTES:

1. MACHINE ENGRAVE BATCH NUMBER.
2. NICKEL PLATE .0004 - .0006, BAKE AFTER PLATING.
3. BREAK ALL SHARP EDGES AND CORNERS .020.

USED ON
20NR
8NR

<b>DART AEROSPACE</b>	
TITLE <b>LOCK</b>	
DWG NO. <b>20NR-61</b>	REV <b>7</b>
MAT'L 4140/4142 HEAT TREAT RC 30-32 FINISH SEE NOTE 2 SPEC DRAWN BY: CANAM CHECKED: SM 04/10/2017 OPPTS APPR: AA 04/10/2017 QA APPR: JL 04/10/2017 APPROVED: JAG 04/13/2017	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX $\pm$ .005 FRACTIONS $\pm$ 1/8 .XX $\pm$ .01 ANGLES $\pm$ 5° .X $\pm$ .1 SURFACES = 125° 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
USED ON MODEL	
SCALE 1:2	DATE 5/20/1997
SHEET 1 OF 1	

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS
			20NR-61	1	LOCK	4140/4142	